

## ROBOMAX JD™ SPECIFICATIONS

Conveyor .....	Rubber / Mintex
Cutting Head .....	Full Floating Cutter Head
Width of Cut .....	16" (406 mm) / 23" (584 mm) / 24" (610 mm)
Length of Cut .....	up to 100" (2540 mm)
Thickness of Cut .....	Hydraulically Adjustable
Pallet Size .....	48" (1.2 m) x 48" (1.2 m), 1.0 m x 1.2 m, 0.8 m x 1.2 m
Cutter Drive .....	Variable Hydraulic
Conveyor Drive .....	Variable Hydraulic
Cutting Blades .....	Standard with Fingers / V-Blade
Construction .....	High Strength Steel Weldment
Total Weight .....	21604 lbs. (9820 kg.)
Overall Length .....	270" (6858 mm)
Overall Width .....	168" (4267 mm)
Transport Width .....	140" (3556 mm)
Overall Height .....	103" (2616 mm)
Pallet Configuration .....	Pyramid or Flat Top
Flap Control .....	Upper Level Squeeze Function Automatic

## TRACTOR SPECIFICATIONS

John Deere .....	6105M / 6110M
Power .....	6105 105 HP Engine
Transmission .....	24 Speed AutoQuad PLUS
Steering .....	Hydrostatic Power
Traction .....	Standard 4WD
Front Tires .....	400/55-225 Flotation
Rear Tires .....	650/55 R26.5 Flotation Radial
Engine .....	4.5L PowerTech Single Variable Geometry Turbocharger
Cab .....	Deluxe Cab
Seat .....	Deluxe Swivel Air Suspension w/Training Seat



KESMAC INC.  
 TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744  
 US Parts TEL: 1-800-314-1008  
 23324 Woodbine Avenue, Keswick, Ontario L4P 3E9  
 email: info@kesmac.com • www.brouwerturf.com



Watch the Video on YouTube

Specifications subject to change without notice or obligation.  
 Printed in Canada 01/16



*Setting New Standards Worldwide*  
*Turf Industry Leaders in Service and Innovation*





